

# AUTO-TORQ™ 10K POWER UNIT



## MODEL 610A

**SUPER HIGH SPEED HYDRAULIC TORQUE  
WRENCH PUMP  
SUITED FOR DEMANDING TURNAROUND AND  
SHUTDOWN MAINTENANCE OPERATIONS**

### FEATURING:

- \* 6 HP AIR MOTOR
- \* POSITIVE DISPLACEMENT RECIPROCATING FLUID END
- \* 10,000 PSI OPERATION
- \* CIM FLOW DATA: 550 @ 0 PSI, 380 @ 5000 PSI, AND 150 @ 10000 PSI
- \* PRECISION VALVE FOR TORQUE AND PRESSURE CONTROL ADJUSTMENT
- \* GLYCERIN FILLED EASY TO READ PRESSURE GAUGE
- \* AIR INLET FILTER, REGULATOR, LUBRICATOR ASSEMBLY
- \* 3-GALLON HYDRAULIC RESERVOIR
- \* SPIN-ON 10-MICRON OIL FILTER
- \* OIL GAUGE
- \* TEMPERATURE GAUGE
- \* SELF COOLED
- \* LOW MAINTENANCE
- \* RUGGED
- \* HAND HELD TWO BUTTON REMOTE CONTROL PENDANT WITH 25 FEET COLOR-CODED LINES
- \* ALL MOUNTED ON A 2-WHEEL MOBILE HAND TRUCK FOR MAXIMUM PORTABILITY
- \* OPTIONALLY AVAILABLE MOUNTED IN A RIDGED STEEL FRAME
- \* OPTIONALLY AVAILABLE WITH 4 HYDRAULIC PORTS FOR THE SIMULTANEOUS OPERATION OF UP TO 4 TORQUE WRENCHES



Model 610A High Speed Pump

### SAFETY FEATURE:

- \* IF THE BUTTON OF THE REMOTE CONTROL IS RELEASED OR THE REMOTE CONTROL IS DROPPED, THE PUMP AND TORQUE WRENCH WILL COME TO AN IMMEDIATE STOP
- \* EQUIPPED WITH TWIN AIR EXHAUST VALVES

### AIR REQUIREMENT:

- \* REQUIRES 150 CFM AIR VOLUME @ 100 PSI FOR OPTIMUM PERFORMANCE