

AUTO-TORQ™ 10K POWER UNIT



MODEL 610A

**SUPER HIGH SPEED HYDRAULIC TORQUE
WRENCH PUMP
SUITED FOR DEMANDING TURNAROUND AND
SHUTDOWN MAINTENANCE OPERATIONS**

FEATURING:

- * 6 HP AIR MOTOR
- * POSITIVE DISPLACEMENT RECIPROCATING FLUID END
- * 10,000 PSI OPERATION
- * CIM FLOW DATA: 550 @ 0 PSI, 380 @ 5000 PSI, AND 150 @ 10000 PSI
- * PRECISION VALVE FOR TORQUE AND PRESSURE CONTROL ADJUSTMENT
- * GLYCERIN FILLED EASY TO READ PRESSURE GAUGE
- * AIR INLET FILTER, REGULATOR, LUBRICATOR ASSEMBLY
- * 3-GALLON HYDRAULIC RESERVOIR
- * SPIN-ON 10-MICRON OIL FILTER
- * OIL GAUGE
- * TEMPERATURE GAUGE
- * SELF COOLED
- * LOW MAINTENANCE
- * RUGGED
- * HAND HELD TWO BUTTON REMOTE CONTROL PENDANT WITH 25 FEET COLOR-CODED LINES
- * ALL MOUNTED ON A 2-WHEEL MOBILE HAND TRUCK FOR MAXIMUM PORTABILITY
- * OPTIONALLY AVAILABLE MOUNTED IN A RIDGED STEEL FRAME
- * OPTIONALLY AVAILABLE WITH 4 HYDRAULIC PORTS FOR THE SIMULTANEOUS OPERATION OF UP TO 4 TORQUE WRENCHES



Model 610A High Speed Pump

SAFETY FEATURE:

- * IF THE BUTTON OF THE REMOTE CONTROL IS RELEASED OR THE REMOTE CONTROL IS DROPPED, THE PUMP AND TORQUE WRENCH WILL COME TO AN IMMEDIATE STOP
- * EQUIPPED WITH TWIN AIR EXHAUST VALVES

AIR REQUIREMENT:

- * REQUIRES 150 CFM AIR VOLUME @ 100 PSI FOR OPTIMUM PERFORMANCE